

suspended ceiling tile

INSTALLATION INSTRUCTIONS

easy as 1-2-3

Remove existing ceiling tiles (if applicable) and pop any Ceilume Ceiling Tile style into place in the drop ceiling.

In perimeter and border situations where the T-bar sections are irregular or not a full 2' x 2' or 2' x 4' in size, border ceiling tile styles can be easily trimmed to fit using common, household scissors.

drop-out ceiling tiles under fire sprinklers

PLEASE NOTE: FEATHER-LIGHT SERIES ONLY

When used under standard release sprinkler systems rated with an activation temperature of 165°F or above, Ceilume's Feather-Light Ceiling Tiles and AcoustoTherm Backpanels must not be fastened directly to metal T-bar members. They are to be set in place ONLY. No clips, fasteners or impediments of any kind can be used to limit the ceiling tile's ability to drop from the suspension system without restraint in the event of a fire.

In areas where there is exposure to drafts and air currents, hold down clips can be used to limit the ceiling tile's upward movement only - clips must not prevent ceiling tiles and panels from dropping out in the event of a fire.

translucent lighting panels

For best lighting results and lengthened life, translucent ceiling tiles used in lighting applications should be positioned at least 6" below lighting fixtures. It is also recommended that lighting panels be used in conjunction with AcoustoTherm Backpanels, which nest above the translucent ceiling tiles.

These clear backpanels provide better diffusion of light, hide dust and insect accumulation, and increase sound absorption and heat insulation properties.

1-800-521-4261
www.ceilume.com

PATENT PENDING - Installation Instructions Revised: 06/04/2010

 **ceilume**
THE SMART CEILING TILE®

suspended ceiling tile

INSTALLATION INSTRUCTIONS

painting

All Ceilume products can be painted before or after installation. Be sure ceiling tiles are clean and dry and experiment on a sample ceiling tile with your paint of choice before painting the ceiling in its entirety. Do not use solvent type thinner or cleaners.

Painting voids the Class A Fire Rating.

cleaning

Ceilume Ceiling Tiles require no special cleaning agents – just wipe with a soft, damp rag.

There is no risk of water damage during cleaning and there is no need for scheduled professional cleaning and resurfacing to prevent environmental and aesthetic problems.

Small, stubborn spots can be handled with cleaners such as Fantastik® or Windex®.

Cleaners containing organic solvents or other aggressive ingredients should not be used because they may affect the surface appearance of the tile. Examples of such cleaners are chlorine bleach, liquid grease remover, strong soaps and detergents containing organic solvents, nail polish remover and furniture polish/cleaners.

storing

Do not store ceiling tiles in contact with direct sunlight or in contact with any heat that may reach temperatures of over 110°F. When temperatures reach these levels, the vinyl is likely distort.

1-800-521-4261
www.ceilume.com

PATENT PENDING - Installation Instructions Revised: 06/04/2010

**ceilume**
THE SMART CEILING TILE®